4. ADD DEVICES VIA AUTO DISCOVERY

For organizations that deploys a large number of NovoConnect devices, adding a device via auto discovery can save a lot of effort. This function allows IT staff to create and install a custom configuration file to automatically configure NovoConnect's settings via a microSD card.

Generate "NovoAutoConfig.xml" configuration file

 Choose "Device Discovery" and then click "Generate AutoConfig File ...", as illustrated in the figure below.



1. Follow the on-screen instructions to complete the configuration parameters.

\$	Generate Configuration File	×
w	/hich device would you like to set up?	
	NovoPro	•
	NovoEnterprise	
	NovoCast	=
	NovoVue	
	NovoTouch	
	LK Series	-
D	 oes your device have Settings Lock Enabled? Yes Settings Password: 	
	0 No.	
		Next

 The following window will appear and you need to work with your organization's IT staff to obtain the appropriate values for each item, and click on "Save..." to save file "NovoAutoConfig.xml" to a microSD card.

🐞 Generate Configuration File	×
NovoPro - Set	tings Lock Disabled
General	
Edition:	None 🗘
Time Zone:	None 🔷
Language:	None 🔷
Settings Password:	
WiFi	
Security:	None
SSID:	
Screen-Cast Configuration	
	Google Cast: None
	AirPlay: None
	PIN Required: None
Remote Manager	
ID Addross	
IP Address.	
Port Number:	20142 😴
Report Period:	15 🜩 Seconds

Note: Regarding "Port Number" in the figure above, you can change it via menu "Preference", as illustrated below.

눦 Remote Manager							- 🗆 ×	
+ Device 🗇 Device Discovery All Devices (7) Unassigned Devices (2) Group List: + Group Admin Building (2)	Firmware Update	Preferences System Preferences Language English Remote Manage	Preferences V 2.2.1.101 System Preferences Language English		1 © 2015	© 2015 Delta Electronics, Inc. All Rights Reserved. Config Set Moderator 08 10 0 nware Version Group rescript Campus A Campus A		
Campus A (2) Cothers (1)	Admin Hallway A Admin Hallway B Classroom 101 Classroom 102 Meeting Room Bilba	Port Number: 192.168.2.24 192.168.1.2	20142 🜩 Restore Def	OK Cance		Admin Building Admin Building Others		

Apply the configuration to a NovoConnect device:

 Insert the microSD card with NovoAutoConfig.xml file to a NovoConnect device, and then the following pop-up will appear on the home screen of the NovoConnect device. There is a 30-second timeout window that you can verify the parameters are set with the proper values. Then the device will be configured with those new settings automatically.



 After the new settings take effect, the NovoConnect device will automatically report its existence to the Remote Manager. You can click on "Device Discovery" and then "Discover Devices" to bring up a discovery dialog window, where you will be able to view live NovoConnect devices and add them to the device list of the Remote Manager.

🐞 Remote	Vlana	ger									
+ Device	Ê De	evice Disc	ice Discovery 🛛 🤂 Firmware Update 🛛 🔅 Prefe			,	V 2.2.1.1	.01 © 20	15 Delta Electronics	, Inc. All Rights Res	served.
All Devices (6)		🏷 Repo	orting Devices S	erver [192.168.2	7:20142, 172.18	.69.112:20142]		_	-		
Unassigned De	evices								😋 Refresh 🛛 📀 Ex	port	riptior
			ID	Name	Version	Mac Address	WIFI Mode	SSID	WIFI IP Address	LAN IP Address	
Group List:			Novo-17D76C70	3 Novo-6C703	v2.2.0.159	04:E6:76:BC:C6:39	WiFi Client mode	phishnet		172.18.69.124	
Admin Building Campus A (2) Others (1)	Building (2) is A (2) s (1)										
		•				111				Þ	

< Back